

Technical Data Sheet

CertainTeed Metal Roofing – Slate



Product Information

CertainTeed Slate metal roofing is authentically crafted, light-weight, fully recyclable, energy efficient and forged in steel. Each panel is comprised of a carbon alloy steel core, with hot-dipped G90 Zinc Phosphate anti-corrosion coating, plus an exterior PVDF Paint System. With its colors designed to recreate the hues of natural slate, CertainTeed Slate adds a warm, custom-crafted appearance to your home.



Colors Available

Storm Slate Mountain Sage Cobalt Castle Gray Brownstone

Physical Properties

Gauge	Thickness
28	0.016"

Panel Dimensions (Nominal):

Panel	Width [in]	Length [in]	Thickness [in]	
			Lower Edge	Upper Edge
Uninstalled	22-1/8	47-1/2	3/8	3/16
Installed/Exposed	20-1/2	45-7/8	3/8	3/16

Roof Coverage:

Panels / Square [nominal]	Panels / Square [actual]	Cartons / Square [nominal]	Weight / Square [lb]
16	15.3	2	96

1 Square = 100 sq ft

Packaging and Shipping Information:

Panels / Carton [ea]	Weight / Carton [lb]	Cartons / Pallet [ea]
8	45	40

Weight / Pallet [lb]	Pallets / TL [ea]	Weight / TL [lb]
1,800	22	39,600

Code Evaluations

Certifying Body	Report ID	Compliance
IAPMO	ER-375	ICC-ES AC166
		2015, 2012, 2009 IBC
		2015, 2012, 2009 IRC
Texas Dept. of Insurance	RC-487	IBC/IRC with Texas Revisions

Performance Properties

Description	Standard
Impact Resistance	UL 2218 Class 4
Gravity Load Resistance	ASTM E72
Weathering Resistance	IBC 1504.6 / ASTM G-154
Wind-Driven Rain	AC166 (Sec. 4.2)

Wind Resistance

Wind Uplift Resistance:

Fastening Method	MAXIMUM ALLOWABLE UPLIFT LOADS [psf]
No. 10 by 1 1/2-inch zinc-coated panhead screws one in each of the 4 holes along the panel fastening edge - 4 fasteners/panel	33 psf
No. 10 by 1 1/4-inch zinc-coated panhead screws 7 inches on center along the top fastening edge	42 psf

Design Wind Speed:

- Under the 2009 IBC, 2009 IRC, and 2012 IRC, CertainTeed Metal Roofing is prescriptively recognized for use at locations where the maximum nominal design Basic Wind Speed, 3-second gust, as described on the Basic Wind Speed maps contained in those codes, is 100 mph (161 km/h), in Exposure B areas, on structures a maximum of 40 feet (12 192 mm) in height.
- Under the 2012 IBC, 2015 IBC, and 2015 IRC, CertainTeed Metal Roofing is prescriptively recognized for use at locations where the maximum Ultimate Design Wind Speed, V_{ULT} , 3-second gust, as described on the Ultimate Design Wind Speed maps contained in those codes, is 130 mph (209 km/h), in Exposure B areas, on structures a maximum of 40 feet (12 192 mm) in height.

Fire Resistance / Approved Systems

ASTM E108 Class A:

Assembly No. 1	
BOTTOM LAYER	¼" or ½" Georgia Pacific DensDeck
TOP LAYER (choose one):	CertainTeed MetaLayment®; or CertainTeed WinterGuard® HT; or CertainTeed DiamondDeck®

ASTM E108 Class A:

Assembly No. 2 / with UNDERLAYMENT	
BOTTOM LAYER:	GAF VersaShield
TOP LAYER (choose one):	CertainTeed MetaLayment; or CertainTeed WinterGuard HT; or CertainTeed DiamondDeck

Fire Resistance / Approved Systems (continued)

ASTM E108 Class B:

Assembly No. 3	
Underlayment (choose one):	CertainTeed MetaLayment; or CertainTeed WinterGuard HT; or CertainTeed DiamondDeck; or All Weather Empire Base (CT); or GAF VersaShield

IMPORTANT: For roof slopes from 3:12 up to 4:12, CertainTeed WinterGuard HT, CertainTeed MetaLayment or equivalent high temperature resistant self-adhering underlayment must be installed over the entire deck. Ensure deck underside is properly ventilated.

Application Instructions

Apply CertainTeed Slate shingles following the method described in CertainTeed’s installation guide which can be found at CertainTeed.com or by contacting CertainTeed at 1-800-233-8990. Roof slope must be 3:12 or greater. Roof deck must be a minimum 15/32” thick solid APA plywood or equivalent. CertainTeed WinterGuard HT, CertainTeed MetaLayment or equivalent high temperature resistant self-adhering underlayment must be installed directly to the deck (or fire resistant barrier) on all eaves and in all valleys. CertainTeed’s DiamondDeck synthetic underlayment, or its equivalent, must be applied to the balance of the roof deck.

Accessory Products

Refer to Shake / Slate Accessory Brochure

Limited Warranty

CertainTeed warrants to the original homeowner that, when subject to normal and proper use, its CertainTeed painted metal roof shingles (a) will be free from manufacturing defects; (b) will not peel, flake, chip, or crack; (c) will meet UL 2218 Class 4 impact resistance; (d) will resist wind uplift damage in winds up to 130 miles per hour; and (e) will not, after removal of foreign surface deposits, chalk more than eight (8) Hunter ΔE (color difference) units, and all paint colors which are contained on the surface will not fade under normal weathering more than five (5) Hunter ΔE units. Color difference units are determined by ASTM D2244. Chalk erosion ratings are determined by ASTM D4214, Method A. The Limited Warranty remains in effect for as long as the original homeowner owns the residence where CertainTeed Metal shingles were originally installed. See actual Limited Warranty for full details.

CertainTeed Shake, Slate and Tile accessory products carry a limited warranty against manufacturing defects concurrent with the warranty of the field shingle with which it is installed.

CertainTeed Roofing

20 Moores Road, Malvern, PA 19355

© Copyright CertainTeed Corporation, 2016
All rights reserved. Updated: 03/2018

